

Energy Flow UPS



- Pure sine wave inverter
- Selectable input voltage range for home appliances and personal computers
- Selectable charging current
- Auto restart while AC is recovering
- Overload and short circuit protection
- Generators & Computer-related devices compatible
- Smart battery charger design for optimized battery performance
- Cold start function

Energy Flow UPS Selection Guide

MODEL	UPS EF 700	UPS EF 1.2K
CAPACITY	700 VA / 500 W	1200 VA / 840 W
INPUT		
Voltage	230 VAC	
Selectable Voltage Range	170-280 VAC (For Personal Computers) 90-280 VAC (For Home Appliances)	
Frequency Range	50/60 Hz (Auto sensing)	
OUTPUT		
AC Voltage Regulation (Batt. Mode)	230VAC \pm 5%	
Surge Power	1400 VA	2400 VA
Efficiency (Peak)	90%	
Transfer Time	10 ms (For Personal Computers) 20 ms (For Home Appliances)	
Waveform (Batt. Mode)	Pure sine wave	
BATTERY & AC CHARGER		
Battery Voltage	12 VDC	
Floating Charge Voltage	13.5 VDC	
Low Battery Alarm Voltage	11.5 VDC	
Shutdown Voltage	10.5 VDC	
Overcharge Protection	15 VDC	
Maximum AC Charge Current	10 A or 15 A	10 A or 20 A
PROTECTION		
Full Protection	Overload and short circuit protection	
PHYSICAL		
Dimension, D X W X H (mm)	289 x 290 x 127	
Net Weight (kgs)	4.5	4.8
ENVIRONMENT		
Humidity	0 to 90% Relative Humidity (Non-condensing)	
Operating Temperature	0°C to 50°C	
Storage Temperature	-15°C to 70°C	

Product specifications are subject to change without further notice

Energy Flow GmbH

Germany: 4 Friedrichstraße,
45128 Essen, NRW
Bulgaria: 12 Gen. Skobelev Str.,
6100 Kazanlak, Stara Zagora

GSMs: Martin Zhelev +359 885 74 44 50
Stoyan Zhelev +359 887 26 28 27
Volen Makedonski +359 899 10 99 69
Fax: +359 431 6 44 28
e-mail: energyflow.org@gmail.com
website: www.energy-flow.org
www.ef-panles.com